

2570

SAE J1402 FMVSS106



# Part Number	Hose I.D.		Hose O.D.		Maximum Operating Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight of Hose	
	mm	in.	mm	in.	bar	psi	bar	psi	mm	in.	Kg/m	lbs/ft
2570-6	9,7	0.38	19,1	0.75	16,0	225	62,0	900	44,5	1.75	0,27	0.18
2570-8	12,7	0.50	22,4	0.88	16,0	225	62,0	900	50,8	2.00	0,34	0.23
2570-10‡	15,7	0.62	26,9	1.06	16,0	225	62,0	900	57,2	2.25	0,44	0.30

Construction
Synthetic rubber tube, double textile braid and synthetic rubber cover.

Operating Temperature Range
-40°C to +100°C [-40°F to +212°F]

Application
Tractor to trailer lines, axle chamber lines and tractor service lines. For more information on specific fluid applications and high temperature ratings, see pages 349-355.

For Complete Agency Listings
See pages 346-348.

‡ *Crimp Fittings only, contact Eaton Aeroquip.*

Fitting Reference	Page
<i>Reusable</i>	
Fitting	182
Socket Data	65

Factory crimp fittings also available. Contact Eaton for details.