

FC273

Six Spiral Wire

SAE 100R13, EN 856 Type R13, ISO 3862 Type R13



# Part Number	Hose I.D.		Hose O.D.		Maximum Operating Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight of Hose	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
FC273-20	31,8	1.25	49,8	1.96	350,0	5100	1400,0	20400	420,0	16.50	3,66	2.46
FC273-24	38,1	1.50	57,4	2.26	350,0	5100	1400,0	20400	500,0	20.00	4,70	3.16
FC273-32	50,8	2.00	71,1	2.80	350,0	5100	1400,0	20400	640,0	25.00	7,11	4.78

Construction

Synthetic rubber tube, 6-heavy wire spiral reinforcement and DURA-TUFF™ rubber cover.

Operating Temperature Range

-40°C to +121°C [-40°F to +250°F]

Application

Hydraulic system service with petroleum and water-base fluids, for general industrial service. For more information on specific fluid applications and high temperature ratings, see pages 349-355.

For Complete Agency Listings

See pages 346-348.

Fitting Reference

Crimp	Page
Spiral TTC	97
Single Skive	113
Internal Skive	123
Socket Data	64