

150901
Large Bore
Meets MIL-H-24135/4



PART NUMBER	HOSE I.D.	HOSE O.D.	MAXIMUM OPERATING PRESSURE	MINIMUM BURST PRESSURE	MINIMUM BEND RADIUS	VACUUM SERVICE	WEIGHT PER FOOT
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
150901-40	2.50	3.09	1200	4800	26.00	Coil*	2.97
150901-48	3.00	3.59	900	3600	30.00	Coil*	3.33
150901-64	4.00	4.70	600	2400	33.00	Sleeve*	3.69

FITTING REFERENCE	PAGE
Dogleg	88
Flange	89-99
Split Clamp	100-103
180° Return	104
<i>Accessories see page Assembly</i>	149-152
<i>Instructions see page</i>	170

Construction: Synthetic rubber tube, textile inner braid (-64 size only), double steel wire braids reinforcement and synthetic rubber cover.
Application: Petroleum based products, particularly fuel and lube oils, salt and fresh water. Approved for Technical Directive for Piping Devices – Flexible Hose Assemblies, S6430-AE-TED-010, Volume 1. For more specific information on fluid compatibility, **see page 176.**
Operating Temperature Range: -40°F to +200°F (-40°C to +93°C).
 *Internal support coil or sleeve is required.