



Charleston Rubber & Gasket also assembles Anhydrous Ammonia hose from stainless steel hose and fittings.

# 1" x 12' Nylon Braid Reinforced Anhydrous Ammonia (NH3) Hose Assembly

## Part# 98108250

Designed to handle anhydrous ammonia to 350 PSI working pressure with a 5:1 safety factor (1750 PSI minimum burst). Degradation resistant, nylon reinforcement provides flexibility with high tensile strength. High quality synthetic compound cover provides excellent ozone and abrasion resistance. Compatible with N-Serve® when used in recommended concentrations. All assemblies have crimped and certified male pipe thread fittings attached to both ends, plus pin-pricked covers to prevent delamination. Meets or exceeds RMA/TFI/ANSI.

[Print Page](#) [Email Page](#)

SPECIFICATIONS
<b>EAN / UPC:</b> 725559088100
<b>Inside Diameter (in):</b> 1
<b>Inside Diameter (mm):</b> 25.4
<b>Outside Diameter (in):</b> 1.5
<b>Outside Diameter (mm):</b> 38.1
<b>Maximum PSI:</b> 350
<b>Minimum Bend Radius (in):</b> 10
<b>Fittings:</b> Male Pipe Thread x Male Pipe Thread Crimped
<b>Temperature Range:</b> -40°F to 180°F
<b>Cover Material:</b> EPDM
<b>Cover Color:</b> Black
<b>Tube Material:</b> EPDM
<b>Tube Color:</b> Black
<b>Reinforcement:</b> 2 Nylon Braids
<b>Weight (lbs):</b> 7.92 / Each
<b>Style:</b> Coiled
<b>Notes:</b> Do not use Anhydrous Ammonia hose in LP Gas, Natural Gas, or refrigeration applications.

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)