

FC162
High Pressure
Meets MIL-H-24135/2



PART NUMBER	HOSE I.D.	HOSE O.D.	MAXIMUM OPERATING PRESSURE	MINIMUM BURST PRESSURE	MINIMUM BEND RADIUS	VACUUM SERVICE	WEIGHT PER FOOT
	INCHES	INCHES	PSI	PSI	INCHES	INCH/Hg	POUNDS
#							
FC162-06	.38	.84	4500	18000	5.00		.46
FC162-08	.50	.97	4000	16000	7.00		.52
FC162-12	.75	1.23	3000	12000	9.50	Coil*	.82
FC162-16	1.00	1.56	3000	12000	11.00	Coil*	1.25

FITTING REFERENCE	PAGE
SAE 37°	75
CPV	76-77
Dogleg	78
Steel	79-82
<i>Accessories see page Assembly</i>	149-152
<i>Instructions see page</i>	168

Construction: Synthetic rubber tube, partial textile braid, 4-light spiral wire reinforcement, and synthetic rubber cover.

Application: Hydraulics, fuel and lube oils, salt and fresh water. Particularly recommended for hydraulic systems that have high surge peaks and/or severe operating conditions. For more specific information on fluid applications, **see page 176.**

Operating Temperature Range: -40°F to +200°F (-40°C to +100°C).

*Internal support coil is required.