

HOT TAR & ASPHALT HOSE



Hot Tar & Asphalt Hose is an industrial suction and discharge hose designed to handle high-temperature materials such as hot asphalt, glue, oil, tar and wax to 300°F continuous and 350°F intermittent (149°C/177°C). The hose also handles refined fuels such as biodiesel (to B100 in dedicated service), diesel, ethanol and gasoline. The hose construction incorporates a dual wire helix that provides full suction capability, kink resistance and a path to conduct a static electrical charge to ground. The cover is resistant to abrasion, heat, oil and weathering.

| | | | |
|----------------------|---------------|----------------------|--|
| TUBE MATERIAL | Black nitrile | REINFORCEMENT | Two textile plies with dual wire helix |
| COVER | Wrapped | TEMPERATURE | -20°F to 350°F |

| I.D. | O.D. | WORKING PRESSURE (PSI) | VACUUM (IN/HG) | MINIMUM BEND RADIUS | WEIGHT / FT |
|------|-------|------------------------|----------------|---------------------|-------------|
| 2" | 2.72" | 150 | 29 | 10" | 1.8 lbs |
| 3" | 3.78" | 150 | 29 | 15" | 2.94 lbs |
| 4" | 4.80" | 150 | 29 | 20" | 3.89 lbs |

INDUSTRY INTERCHANGE: Pyroflex, SS387