

MATERIAL SUCTION HOSE

Hard-wall hose designed with a high abrasion-resistant tube. Ideal for applications where suction and/or discharge of abrasive media is required. Can be crimped or banded to make assemblies per your specifications.



TUBE	Gum rubber or gum rubber blend	REINFORCEMENT	Fiber cord plies, helical wire
COVER	SBR	TEMPERATURE	-40°F to 185°F

I.D.	O.D.	WORKING PRESSURE (PSI)	VACCUM (IN/HG)	MIN. BEND RADIUS	WEIGHT/FT (LBS)
1 1/4"	1.81"	75	29	4"	0.77
1 1/2"	2.1"	75	29	4"	1.11
2"	2.6"	75	29	12"	1.3
2 1/2"	3.11"	75	29	17"	1.65
3"	3.66"	75	29	18"	2.25
4"	4.69"	75	29	24"	2.93
5"	5.7"	75	29	30"	3.83
6"	6.73"	75	29	32"	5
8"	9.13"	60	29	40"	10.05

MATERIAL DISCHARGE HOSE

Soft-wall hose designed with a high abrasion-resistant tube. Ideal for applications where discharging of abrasive media is required. Can be crimped or banded to make assemblies per your specifications. Available in 1/8" 3/16" and 1/4" tube.



TUBE	Nitrile/SBR blend, static dissipating	REINFORCEMENT	Fiber cord plies
COVER	SBR	TEMPERATURE	-40°F to 185°F

I.D.	O.D.	WORKING PRESSURE (PSI)	VACCUM (IN/HG)	MIN. BEND RADIUS	WEIGHT/FT (LBS)
4"	4.68"	75	N/A	40"	2.42
5"	5.68"	75	N/A	50"	2.92

* 3/16" thick tube shown.

INDUSTRY INTERCHANGE: Black Softwall, SS147, 609W, Lynx

* RAGCO supports the autonomy of its locations to select the best products to service their markets. Subtle variations of these specifications may exist. Contact your RAGCO affiliate for confirmation.

RUBBER HOSE

