## **UFD** Series Hoses



TEMPERATURE RANGE: -65° F to 200° F

**CONSTRUCTION**: Polyurethane reinforced with a wire helix

STANDARD COLORS: Clear or Black STANDARD LENGTHS: 25', 50'

SIZE RANGE: 2" to 18"

- · Superior abrasion resistance
- · Excellent flex fatigue resistance
- · Clear version allows users to locate blockages
- · Handles higher pressure and vacuums than standard ducting
- FDA materials are available upon request
- · Available with cuffed end finishes
- · Available in metric diameters, consult us on minimums



TEMPERATURE RANGE: -65° F to 200° F

**CONSTRUCTION**: Polyurethane reinforced with a wire helix

STANDARD COLOR: Clear STANDARD LENGTHS: 25', 50'

SIZE RANGE: 2" to 12"

- · Lightweight alternative to UFD
- · Excellent flexibility
- Transparency of UFD.020-Clear allows users to locate blockages
- FDA materials are available upon request
- · Ideal for oil mist applications
- · Available with cuffed end finishes



TEMPERATURE RANGE: -65° F to 200° F

CONSTRUCTION: Heavy walled polyurethane reinforced

with a wire helix

STANDARD COLOR: Clear STANDARD LENGTHS: 25', 50'

SIZE RANGE: 2" to 18"

- Superior abrasion resistance
- The color of the hose allows for the user to locate blockages
- Excellent for leaf and lawn collection and other severe service applications
- FDA materials are available upon request
- · Available with cuffed end finishes
- Available in 10' lengths during leaf collection season



TEMPERATURE RANGE: -65° F to 200° F

CONSTRUCTION: Heavier wall polyurethane reinforced

with a wire helix

STANDARD COLOR: Blue STANDARD LENGTHS: 25', 50' SIZE RANGE: 2-1/2" to 18"

- Superior abrasion resistance
- Transparency of UFD.060 allows users to locate blockages
- Excellent for leaf and lawn collection, street sweepers and other severe service applications
- Available in 10' lengths during leaf collection season
- · Available in clear, consult us on minimums
- FDA materials are available upon request in clear