









# 60 Durometer Neoprene Tubing

WARCO BILTRITE's 60 Durometer Neoprene Tubing is Anti-Fungal per Mil-Std-8.10 and is designed to meet the Mil-R-6855 Class 2 specification. Compression Set = 50% max. Material is supplied unmarked. For markings, please contact us.

**Color: Black Stock-Item Purchase Minimum: 10 Feet Non-Stock Purchase Minimum: Please call for quote**

Durometer Hardness Shore A $\pm$ 5	Inner Diameter Range inches	Wall Thickness Range inches	Tensile min. psi	Ultimate Elongation min. %	Temperature Range	Specifications
60 060E0713	1/16 thru 5	1/32 thru 1	1500	300	-50°F to +220°F	Anti-Fungal Per Mil-Std-8.10, ASTM G21, Mil-Std-454 Req 4, Mil-R-6855 Class 2 Type A/B Grade 60

The following sizes are stock items:

			
<b>1/4" ID</b> ( $\pm$ 0.010)	<b>5/16" ID</b> ( $\pm$ 0.011)	<b>3/8" ID</b> ( $\pm$ 0.013)	<b>1/2" ID</b> ( $\pm$ 0.016)
<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)
			
<b>9/16" ID</b> ( $\pm$ 0.017)	<b>5/8" ID</b> ( $\pm$ 0.018)	<b>21/32" ID</b> ( $\pm$ 0.019)	<b>3/4" ID</b> ( $\pm$ 0.021)
<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)	<b>1/16" Wall</b> ( $\pm$ 0.009)

<b>1/16"</b> ( $\pm$ 0.009) Wall Thickness		Durometer Hardness (Shore A $\pm$ 5)
		<b>60 Duro</b> 060E0713
Inner Diameter (inches)	<b>1/4"</b> ( $\pm$ 0.010)	<b>\$0.75</b> 31265091
	<b>5/16"</b> ( $\pm$ 0.011)	<b>\$0.90</b> 31267792
	<b>3/8"</b> ( $\pm$ 0.013)	<b>\$0.97</b> 31267793
	<b>1/2"</b> ( $\pm$ 0.016)	<b>\$1.28</b> 31265092
	<b>9/16"</b> ( $\pm$ 0.017)	<b>\$1.45</b> 31265093
	<b>5/8"</b> ( $\pm$ 0.018)	<b>\$1.63</b> 31265094
	<b>21/32"</b> ( $\pm$ 0.019)	<b>\$1.76</b> 31267794
	<b>3/4"</b> ( $\pm$ 0.021)	<b>\$2.16</b> 31265095

Prices are per foot (\$/ft). \$10.00 Min.

► = Regularly Stocked Items.

Please contact us for stencilling, other dimensions, profiles or polymers and for orders over \$500.00  
Call 714-532-3355 or email sales@warco.com

## Neoprene Cable Jacket Tubing to Mil-R-6855 Class 2 Type A/B Grade 60

Protects wires and cables from abrasion, corrosion and the elements. Designed to fit loose or be blown on to wire bundles for a tight fit. WARCO BILTRITE carries compound in stock for a shorter production lead time.

**Color: Black Purchase Minimum: \$500.00 per line item**

Durometer Hardness Shore A $\pm$ 5	Inner Diameter Range inches	Wall Thickness Range inches	Tensile min. psi	Ultimate Elongation min. %	Temperature Range	Specifications
60 060E0055	1/16 thru 5	1/32 thru 1	1500	300	-50°F to +220°F	Mil-R-6855 Class 2 Type A/B Grade 60

Catalog Pricing is available on the following pages for the Wall Thicknesses below:

						
<b>1/32" Wall</b>	<b>3/64" Wall</b>	<b>1/16" Wall</b>	<b>3/32" Wall</b>	<b>1/8" Wall</b>	<b>5/32" Wall</b>	<b>3/16" Wall</b>